

PRELIMINARY

L-CASE II TRANSPORT & OPERATION CASE



L-CASE II is designed to offer a high level of protection against shocks, vibration, water and dust to L-Acoustics amplified controllers, including LA7.16, during their transport, storage and operation. It offers easy and comfortable handling.

Stacked or Flown

L-CASE II can be conveniently stacked on top of each other and secured together with the side velcro tabs. The front tab can be flipped over to the side of the unit to allow access to the control panels and the ventilation of electronics during operation. As for the rear tab, it can either be flipped over to leave access to the rear panels or lie on the cables and act as a protection cap. L-CASE II can also be quickly and securely flown with a safety sling passing through the handle and connected to the electronics chassis.

Shock and vibration protection

L-CASE II protects electronics against shocks during transport and handling thanks to its metallic shell, a dual tubular structure assembled and reinforced with 4 welded U profiles. Protection against vibrations is ensured by two blocks of ultra high density foam acting as internal side panels. Securely braced between the two shell tubes, they act as a "silent-block" absorber.

Easy transport and safe storage

A sleek and ergonomic handle located on one side allows easy transport. The handle is designed not to be too protruding to avoid risks of being hooked to objects.

Water resistant design

The outer protection of electronics against dust, water and dents is ensured by a triple-layered fabric consisting of PVC coated cordura, high density 10 mm reticulated foam and a PVC coated nylon lining. This fabric wraps around the rack shell.



SPECIFICATIONS

General

Capacity Single 2U amplified controller

Construction

Frame Steel tubes with anti-corrosion coating

Padding Ultra-high density foam

Fabric Poly 1300 Cordura® coated with PVC

Safety sling Stainless steel

Physical data

Height x Width x Depth 557 mm x 118 mm x 597 mm
21.9 in x 4.6 in x 23.5 in

Weight (net) 3.8 kg / 8.4 lb (Empty)

with LA7.16 19.6 kg / 43.2 lb

with LA4X 15.1 kg / 33.3 lb

with LA12X 18.3 kg / 40.4 lb

