

X4i SHORT THROW POINT SOURCE



X4i is an installation-specific miniature point source system designed for short throw applications. Part of the X Series, X4i is a 4" format loudspeaker that provides exceptional output and broad bandwidth for its size, ensuring premium sonic performance in an extremely compact enclosure.

X4i is a two-way passive enclosure with transducers mounted coaxially to produce a 110° axisymmetric directivity with a smooth tonal response free of secondary lobes over the entire frequency range. Housed in a cabinet made of first grade Baltic birch plywood, X4i weighs only 1 kg / 2.2 lb and is extremely shallow - less than 10 cm / 4 in - to fit within the depth allowed by conventional construction.


The combination of minimalist dimensions, flexible accessories, white and RAL architectural programs and an IP55 rating make for an easy integration in any situation. On its own, X4i is an ideal complement to larger systems in venues that require seamless integration in the smallest spaces such as theaters, houses of worship, corporate facilities and studios. Supplemented by a subwoofer, X4i is also perfect as a distributed background music system, indoor or outdoor, in bars, restaurant, conference rooms, museums and other hospitality venues.

SPECIFICATIONS


Description	2-way passive coaxial enclosure amplified by LA7.16i / LA2Xi / LA4X / LA12X	
	Preset [X4_60]	Preset [X4]
Usable bandwidth (-10 dB)	65 Hz - 20 kHz	120 Hz - 20 kHz
Maximum SPL¹	110 dB	116 dB
Nominal directivity (-6 dB)	110° axisymmetric	
Transducers	LF: 1 × 4" neodymium HF: 1 × 1.4" diaphragm neodymium compression driver	
Acoustical load	Closed enclosure	
Nominal impedance	16 Ω	
Connectors	IN: 1 × 2-point screw terminal LINK: 1 × 2-point screw terminal Connector sealing plate with cable gland	
Rigging and handling	X4i: 2 M5 inserts on the side for X-U4i / X-B4i X4i: 2 M6 inserts on the rear for on-wall and on-ceiling accessories (X4i-onCW) X4r inWall / inTile recessed versions	
Safety	1 M6 insert on the back for secondary safety	
Weight (net)	1 kg / 2.2 lb	
Cabinet	Premium grade Baltic birch plywood	
Front	Steel grill with anti-corrosion coating	
Finish	Dark grey brown Pantone 426C Pure white RAL 9010 Custom RAL code on special order	
IP	IP55 ²	

¹- Peak level at 1 m under free field conditions using pink noise with crest factor 4 (preset specified in brackets).


² - With connector sealing plate



Front



Side



Top